


Tech Specs

UniFi UISP Branding

60 GHz Wireless Wireless Fiber Wired Accessory Tech

Wired > UISP Router

Datasheet Installation Guide Marketing Images



Mechanical

 $\textbf{Dimensions} \hspace{35mm} 210.4 \times 95 \times 29 \hspace{1mm} \text{mm} \hspace{1mm} (8.3 \times 3.7 \times 1.1")$

Weight 600 g (1.3 lb)

Enclosure material Polycarbonate

Hardware

Management interface

Processor Dual-core 880 MHz, MIPS1004Kc

 Memory
 512 MB DDR3

 Onboard flash storage
 512 MB NAND

 Networking interface
 (8) GbE RJ45 ports (1) 1G SFP port

Ethernet In-Band Bluetooth BLE

Power method External AC/DC adapter

Power supply 27V DC, 4.4A power adapter (included)

Supported voltage range 24—28V DC

 Max. power consumption
 10W (Excluding PoE output)

 ESD/EMP protection
 Air: ± 15kV, contact: ± 8kV

 Operating temperature
 -10 to 50° C (14 to 122° F)

 Operating humidity
 5 to 95% noncondensing

Certifications CE, FCC, IC

PoE

PoE interface (8) 27V passive PoE: 2-pair (pins 4, 5+/7, 8-) or 4-pair (pins 1, 2, 4, 5+/3, 6, 7, 8-)

 $\begin{tabular}{lll} \begin{tabular}{lll} \begin{$

LEDs

System Status

RJ45 data ports PoE

Speed/link/activity

SFP data port Link/activity

Software

Management application UISP: Version 1.4.0 and later

Compliance Information





Terms and Conditions | Terms of Service | Privacy Policy | Return Policy | Cookies Settings

© 2024 Ubiquiti, Inc. All rights reserved.