



Mechanical

Dimensions	442.4 x 325 x 43.7 mm (17.4 x 12.8 x 1.7")
Weight	Without mounting brackets: 5.1 kg (11.3 lb) With mounting brackets: 5.2 kg (11.5 lb)
Enclosure material	SGCC steel
Mount material	SGCC steel

Hardware

Management interface	Ethernet In-Band
Networking interface	(1) GbE RJ45 port (1) 1/10 GbE SFP+ port
Power method	(1) Universal AC input, 100—240V AC, 2A Max., 50/60 Hz (1) USP-RPS DC input, 11.5V DC, 10.43A
Power supply	AC/DC, internal, 120W
Supported voltage range	100—240V AC
Max. power consumption	100W
Max. power budget for Drives	75W
ESD/EMP protection	Air: ± 12kV, contact: ± 8kV
Operating temperature	-5 to 40° C (23 to 104° F)
Operating humidity	5 to 95% noncondensing
Certifications	FCC, CE, IC

LEDs

System	(1) Power: blue/white Flashing white: bootup in progress Flashing blue: firmware upgrading Steady white: factory defaults, awaiting adoption Steady blue: device is adopted
Ethernet	Green: 1 Gbps Amber: 10/100 Mbps
SFP+	White: 10 Gbps Green: 1 Gbps
HDD	White: disk detected Amber: disk error
RPS	Blue: ready

Stay in Touch

Email

Subscribe

