

Tech Specs

UniFi UISP Branding

UniFi Cloud Gateways WiFi Switching Cloud Keys & Gateways Camera Security Door Access Phone System New Integrations Accessories

Switching > Lite 8 PoE

Installation Guide Datasheet Marketing Images







* With an external 60W power adapter

Mechanical

99.6 x 163.7 x 31.7 mm (4 x 6.4 x 1.3") Dimensions

295 g (10.4 oz) Weight

Enclosure material Plastic

Hardware

Supported voltage range

Management interface Ethernet In-Band (8) GbE RJ45 ports Networking interface

(4) PoE/PoE+ (Pins 1, 2+; 3, 6-) PoE interface

Total non-blocking throughput 8 Gbps Switching capacity 16 Gbps

54V DC, 1.1A power adapter Power method

Power supply 54V, external, 60W

Max. power consumption 8W (Excluding PoE output)

Total available PoE 52W*

*With an external 60W power adapter.

50—57V DC

Max. PoE wattage per port by PSE PoE+: 30W Button Factory reset

Operating temperature -15 to 40° C (5 to 104° F) Operating humidity 10 to 90% noncondensing

Certifications CE, FCC, IC

LEDs

System Status

Ethernet PoE

Speed/link/activity

PoE Link/activity

Application Requirements

UniFi Network Version 7.2.94 and later



Terms and Conditions | Terms of Service | Privacy Policy | Return Policy | Cookies Settings

© 2024 Ubiquiti, Inc. All rights reserved.