

Tech Specs

UniFi UISP Branding

UniFi Cloud Gateways WiFi Switching Cloud Keys & Gateways Camera Security Door Access Phone System New Integrations Accessories

Camera Security > G4 PTZ

Datasheet Installation Guide Marketing Images





Mechanical

Dimensions $207 \times 223.7 \times 341.3 \text{ mm } (8.2 \times 8.8 \times 13.4)^{\circ}$

Weight Without mount: 3.8 kg (8.4 lb)

With mount: 6.8 kg (15 lb)

Enclosure materials Metal, plastic

Mount material Metal
Weatherproofing IP66

Optics

Sensor 4K (8MP) 1/1.8" CMOS sensor

Lens 22x optical zoom

 $\begin{tabular}{lll} \begin{tabular}{lll} \begin{$

Night mode Built-in IR LED illumination and IR cut filter

Video

Video compression H.264

Resolution 8MP 3840 x 2160 (16:9)

Max. frame rate 24 FPS

System

Networking interface (1) GbE RJ45 port

 Max. power consumption
 42.9W

 Power method
 PoE++

 Supported voltage range
 42.5—57V

 Button
 Factory reset

Mounting Wall mount (Included)

Operating temperature $$-40\ \text{to}\ 50^{\circ}\ \text{C}\ (-40\ \text{to}\ 122^{\circ}\ \text{F})$}$

Operating humidity 0 to 90% noncondensing

Certifications FCC, IC, CE

Software

Web application UniFi Protect

 Mobile app
 UniFi Protect iOS™ and Android™



Terms and Conditions $\,\mid\,\,$ Terms of Service $\,\mid\,\,$ Privacy Policy $\,\mid\,\,$ Return Policy $\,\mid\,\,$ Cookies Settings

© 2024 Ubiquiti, Inc. All rights reserved.